Technical Data Sheet

315 CONTRACTOR'S GRADE FRICTION TAPE

DESCRIPTION:

15.0 mil insulating tape with cotton cloth backing and non-corrosive rubber-resin adhesive. Very flexible, conformable, abrasion resistant, good tensile strength and hand tearable.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Protection of hanging electric crane wires, harness mechanical protection, pneumatic hose protection on lift trucks, insulating cables that drag on the floor and industrial repair jobs.

CONSTRUCTION:

Backing:	Adhesive:
Cotton cloth	Rubber - Resin

Color:	Standar Lenght:
Black	18mmX20m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Original Adhesion in (cm)	Tensile Strength lb/in (kg/cm)	Elongation %	Dielectric Strength Volts
15 (0.38)	4 (11)	67 (12)	6	1200
Analysis Method:				
IACA-094	*ASTM D69*	*ASTM D-3759*	*ASTM D-3759*	*ASTM D69*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
18/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060