Technical Data Sheet

340 PLASTIC FILM AISLE MARKING TAPE

DESCRIPTION:

Plastic film backing tape with rubber-resin adhesive. Conformable, abrasion resistant, chemical and solvent resistant. Available in multiple solid and striped colors.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Used to delimit traffic areas such as aisles, carpet joints, electrical cables, steps and other facility/safety identification applications.

CONSTRUCTION:

Backing:	Adhesive:
Plastic film	Rubber-Resin

Color:	Standar Lenght:
Black, Yellow, Red, White, Green, Blue, Orange, Purple, Gray, Yellow/Black, White/Black, White/Red, White/Green	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Backing oz/in (g/cm)	Adhesion to Steel oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
6 (0.15)	21 (240)	70 (779)	18 (3.2)	170
Analysis Method:				
IACA-094	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
12/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060