Technical Data Sheet

373 POLYETHYLENE PROTECTION TAPE

DESCRIPTION:

Premium quality polyethylene protection tape. Very conformable, water resistant, easy to unwind, hand tearable, UV resistant up to 30 days, clean removal.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Masking and protection on smooth surfaces such as PVC frames, aluminum, steel, plastic and glass. Flexible, easy to tear by hand, removes cleanly without residue.

CONSTRUCTION:

Backing:	Adhesive:
Polyethylene	Acrylic

Color:	Standar Lenght:
White	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Tensile Strength lb/in (kg/cm)
5 (0.12)	8 (85)	26 (290)	18 (3)

Analysis Method:

IACA-094	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060

12/05/26