# Technical Data Sheet

# 376

# POLYETHYLENE TAPE

## DESCRIPTION:

hyStik 376 is a professional-grade polyethylene film tape coated with an aggressive synthetic rubber pressure-sensitive adhesive. Its durable, moisture-resistant PE backing provides excellent conformability and bonds well to polyethylene sheeting and a wide variety of surfaces. Designed for sealing, splicing, surface protection, restoration, abatement and vapor barrier applications.



*Product presentation may be different than picture.

## SPECIALLY DESIGNED FOR:

Vapor barrier sealing, polyethylene sheeting splicing and patching, construction, restoration, abatement and containment, surface protection, plastic hanging, bundling, wrapping and general industrial repair.

Key Features
- Aggressive adhesion to polyethylene sheeting and multiple surfaces.
- Moisture-resistant polyethylene backing.
- Excellent conformability to irregular surfaces.
- Low water vapor permeance for vapor barrier sealing.
- Durable construction for demanding construction and restoration applications.
- Serrated edge available for easy hand tear.

## CONSTRUCTION:

| Backing: | Adhesive: |
|---|---|
| Polyethylene | Synthetic Rubber |

| Color: | Standar Lenght: |
|---|---|
| Red and White | 48mm x 55m<br>72mm x 55m<br>96mm x 55m |

## PRODUCT ATTRIBUTES:

| Thickness<br>mils (mm) | Adhesion to Steel<br>oz/in (g/cm) | Tensil Strenght<br>lb/in (kg/cm) | Water Vapor Permeance<br>perms | Application Temperature<br>°F (°C) | Opereting Temperature<br>°F (°C) |
|---|---|---|---|---|---|
| 7 (0.18) | 75 (840) | 14 (2.5) | <0.10 | 41F to 122F (5°C to 50°C) | 14F to 176F (14F to 176F) |
| **Analysis Method:** | | | | | |
| *IACA-094* | *ASTM D-3330/M* | *ASTM D-3759* | *ASTM D-3833* | | |

**Note:** All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications.
Customer's entire responsibility is to ensure that product is suitable for the intended use.
**Warranty:** hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060

10/08/26