Technical Data Sheet

378 PREMIUM UV PE MULTI PURPOSE TAPE

DESCRIPTION:

Single coated UV resistant tape for outdoor exposure, made of tough polyethylene backing and synthetic rubber adhesive. Film and adhesive formulated to resist degradation by exposure to UV up to 60 days, leaves no residue upon removal, and maintains watertight seal in all weather conditions.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Used for outdoor exposure applications requiring UV resistance, clean removal, weather resistance, and watertight sealing.

CONSTRUCTION:

Backing:	Adhesive:
Polyethylene	Synthetic

Color:	Standar Lenght:
Red	48mm x 55m 72mm x 55m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)
7 (0.18)	20 (225)	66 (733)	14 (2.5)
Analysis Method:			
IACA-094	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060

14/05/26