Technical Data Sheet

755 1.8 MIL ACRYLIC CARTON SEALING TAPE

DESCRIPTION:

Polypropylene film tape coated with aqueous acrylic adhesive. UV, moisture and cold-weather resistant. Good aging characteristics for long-term use.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Lightweight box sealing, packaging, holding and bundling where moisture resistance is required.

CONSTRUCTION:

Backing:	Adhesive:
BOPP	Emulsion Acrylic

Color:	Standar Lenght:
CLEAR / TAN	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %	Service Temperature °F (°C)	Application Temperature °F (°C)
1.8 (0.045)	25 (279)	20.2 (225)	21 (3.8)	160	0 a 176 (-18 a 80)	32 a 113 (0 a 45)

Analysis Method:

IACA-094	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*	*ASTM D-3759*		

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060

08/05/26