Technical Data Sheet

798

Masking Tape 798 Premium General purpose.



*Product presentation may be different than picture.

DESCRIPTION:

Crepe paper masking tape with rubber-resin adhesive. Very conformable with good tension strenght. It can be used in applications in which baking is required (80°C). Good adhesion tape on tape.

SPECIALLY DESIGNED FOR:

Ideal for using at the office, home o workshop. For easy painting jobs. It can be easily removed without leaving any residues. Test before using.

CONSTRUCTION:

Backing:	Adhesive:
Crepe Paper	Rubber - Resin

Color:	Standar Lenght:
Pale Beige	-

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
5 (0.127)	17.5 (195.3)	28.4 (316.5)	15.7 (2.8)	0.056
Analysis Method:				
IACA - 0194	*ASTM D-3330*	*ASTM D-3330*	*ASTM D-3759*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
11/07/22 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060