

Technical Data Sheet

827

PREMIUM GRADE PAINTING MASKING TAPE

DESCRIPTION:

Crepe paper masking tape with high adhesion rubber-resin adhesive. Very conformable, excellent tensile strength, strong holding, solvent/water/oil resistant and good tape-on-tape adhesion.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Professional automotive body shops and specialized industrial painting applications. Suitable for applications requiring baking temperatures up to 110°C.

CONSTRUCTION:

Backing:	Adhesive:
Crepe Paper	Rubber- Resin

Color:	Standar Lenght:
Yellow / Green / Orange	12x50
	18x50
	36x50
	24x50
	48x50

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Backing oz/in (g/cm)	Adhesion to Steel oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
6.6 (0.168)	24 (185)	16 (260)	18 (3)	600.00%

Analysis Method:

IACA-094	ASTM D-3330/M	ASTM D-3330/M	ASTM D-3759	ASTM D-3759
----------	---------------	---------------	-------------	-------------

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
12/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060