

Technical Data Sheet

835

BLUE PAINTER'S MASKING TAPE – 14 DAY CLEAN REMOVAL

DESCRIPTION:

Long-lasting masking tape with special UV resistant adhesive system. Easy application and clean removal up to 14 days. Resistant to humidity and aggressive solvents.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Indoor and outdoor construction and decoration jobs on glass, vinyl, wood, cement, plaster, aluminum and metal. Do not use on lacquered wood/surfaces, wallpaper or uncured surfaces.

CONSTRUCTION:

Backing:	Adhesive:
Crepe Paper	Rubber- Resin

Color:	Standar Lenght:
Blue	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
6.4 (0.162)	11.6 (255)	22.9 (130)	18.5 (3.3)	8

Analysis Method:

IACA-094	ASTM D-3330/M	ASTM D-3330/M	ASTM D-3759	ASTM D-3759
----------	---------------	---------------	-------------	-------------

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
12/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060