Technical Data Sheet

877 PREMIUM PAPER FLATBACK TAPE

DESCRIPTION:

This flatback tape is engineered for applications requiring high adhesion to backing and excellent performance in high-temperature environments. It is ideal for splicing operations where strong adhesion and durability are critical.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Blue color provides easy identification when used for splices in a vast variety of materials since cardboard until rough sand paper. Ideal to be used in sealing beams on cardboard to protect flooring materials.

CONSTRUCTION:

Backing:	Adhesive:
Flat Back Paper	Rubber - Resin

Color:	Standar Lenght:
Blue	48mmX50m 72mmX50m 96mmX50m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
9 (0.23)	21.1 (235)	73 (815)	50 (8.9)	3
Analysis Method:				
IACA-094	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
05/06/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060