

Technical Data Sheet

878

SURFACE PRINTABLE 2.0 MIL HOT MELT BOPP TAPE

DESCRIPTION:

Surface printable carton sealing tape designed to be printed without chemicals or corona treatment. Outstanding ink anchorage with most brand inks.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

For use on Siat L33, L36, L233 or equivalent surface tape printers.

CONSTRUCTION:

Backing:	Adhesive:
BOPP	Hot melt

Color:	Standar Lenght:
Clear, White	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Steel Adhesion oz/in (g/cm)	Steel Adhesion oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
2 (0.05)	7.2 (80)	43 (480)	24 (4.3)	170

Analysis Method:

IACA-094	ASTM D-3330/M	ASTM D-3330/M	ASTM D-3759	ASTM D-3759
----------	---------------	---------------	-------------	-------------

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
21/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060