

## DESCRIPTION:

930 Venting tape is a non-woven pressure sensitive tape made with an acrylic adhesive, in combination performing a good outgassing rates applications.

Specially designed for the flooring industry applications, such as seaming tape requiring high vapor permeability the insulated panel manufacturing and foaming of refrigerator production lines to aim polyurethane foam outgassing.



\*Product presentation may be different than picture.

## SPECIALLY DESIGNED FOR:



FLOORING SEAMING



INSULATED PANELS



REFRIGERATOR FOAMING

930, VENTING TAPE, FEB. 2026

## PRODUCT ATTRIBUTES

Thickness mils(mm)	Adhesion to steel oz/in (gr/cm)	Tensile Strength lb/in (kg/cm)	Elongation (%)
<b>4.7 (0.12)</b>	<b>21 (231)</b>	<b>7.3 (1.3)</b>	<b>20</b>

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

## CONSTRUCTION:

STANDARD LENGTH (mm x m)	BACKING	COLOR	ADHESIVE:
48 x 50 72 x 50	NONWOVEN	WHITE	ACRYLIC

### Guarantee:

HyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices. It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.