Technical Data Sheet

970

FILAMENT REINFORCED POLYPROPYLENE TAPE

DESCRIPTION:

Polypropylene tape reinforced with fiberglass filaments. Excellent mechanical properties, high tensile and shear strength, high instant adhesion and strong holding power.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Heavy-duty holding, bundling and sealing of very heavy boxes; securing domestic or industrial equipment during transportation; retail theft protection while preserving barcode readability.

CONSTRUCTION:

Backing:	Adhesive:
BOPP reinforced	Hot melt

Color:	Standar Lenght:
Clear	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
4.4 (0.11)	80.6 (900)	24.1 (270)	110 (20.2)	5
Analysis Method:				
IACA-094	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
11/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060