Technical Data Sheet

313 INDUSTRIAL GRADE FRICTION TAPE

DESCRIPTION:

General purpose black friction tape with cotton cloth backing. Provides mechanical protection against abrasion and penetration of cables, splices and harnesses. Non-slip surface on tool/sport handles.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Mechanical protection for cables, splices and harnesses; non-slip grip surface for tool and sport handles.

CONSTRUCTION:

Backing:	Adhesive:
Cotton cloth	Rubber - Resin

Color:	Standar Lenght:
Black	19mmX9.1m 19mmX18.3m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Original Adhesion oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %	Dielectric Strenght Volts
13 (0.33)	7 (18)	45 (8)	5	1000
Analysis Method:				
IACA-094	*ASTM D69*	*ASTM D-3759*	*ASTM D-3759*	*ASTM D69*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
18/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060