

Technical Data Sheet

hyStik®
adhesive tapes

376

Professional Grade PE Tape for Sealing, Splicing, Surface Protection and Vapor Barrier Applications

DESCRIPTION:

hyStik 376 is a professional-grade polyethylene film tape coated with an aggressive synthetic rubber pressure-sensitive adhesive. Its durable, moisture-resistant PE backing provides excellent conformability and bonds well to polyethylene sheeting and a wide variety of surfaces. Designed for sealing, splicing, surface protection, restoration, abatement and vapor barrier applications.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Vapor barrier sealing, polyethylene sheeting splicing and patching, construction, restoration, abatement and containment, surface protection, plastic hanging, bundling, wrapping and general industrial repair.

Key Features

- Aggressive adhesion to polyethylene sheeting and multiple surfaces
- Moisture-resistant polyethylene backing
- Excellent conformability to irregular surfaces
- Low water vapor permeance for vapor barrier sealing
- Durable construction for demanding construction and restoration applications
- Serrated edge available for easy hand tear

CONSTRUCTION:

Backing:	Adhesive:
Polyethylene	Synthetic Rubber

Color:	Standar Lenght:
Red and White	48mm x 55m
	72mm x 55m
	96mm x 55m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %	Water Vapor Permeance Perms	Application Temperature: °F (°C)	Operating Temperature: °F (°C)
7 (0.18)	75 (840)	14 (160)	14 (2.5)	450	<0.10	41 to 122 (5 to 50)	14 to 176 (14 to 176)

Analysis Method:

IACA-094	ASTM D-3330/M	ASTM D-3330/M	ASTM D-3759	ASTM D-3759	ASTM D-3833		
----------	---------------	---------------	-------------	-------------	-------------	--	--

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications.

Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632

10/08/26

hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060

— HIGH TECHNOLOGY ADHESIVE TAPES —

CONTACT US INFONA@HYSTIK.COM

FOR SAMPLES OR DISTRIBUTOR PRICING!