Technical Data Sheet

377

9 MILS PE TAPE



*Product presentation may be different than picture.

DESCRIPTION:

Heavy-duty tape featuring a polyethylene film backing, single-coated with a synthetic rubber pressure-sensitive adhesive. Provides a watertight seal, humidity resistance, and long-lasting surface protection. Serrated edge enables clean hand tearing, while the high tack adhesive ensures secure bonding.

SPECIALLY DESIGNED FOR:

Specially designed for waterproof sealing, masking windows or doors, stucco and painting.

CONSTRUCTION:

Backing:	Adhesive:
Polyethylene	Synthetic

Color:	Standar Lenght:
Red and White	48mm x 55m 72mm x 55m 96mm x 55m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)
9 (0.22)	28 (312)	80 (889)	17 (3)
Analysis Method:			
IACA-094	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060

14/05/26