

Technical Data Sheet

410

Double Sided Splicing Tape

DESCRIPTION:

Double sided tape, with polyester backing and acrylic adhesive for strong bonds on a variety of surfaces, such as paper and cardboard, including various LSE surfaces. Very flexible and conformable to irregular surfaces.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Used for flying splices in different industrial processes, with manual or automatic application.

CONSTRUCTION:

Backing:	Adhesive:
PET Film	Acrylic

Color:	Standar Lenght:
Black	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Internal Steel Adhesion oz/in (g/cm)	External Steel Adhesion oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %	Temperature °F (°C)
6.2 (0.16)	75 (828)	102 (1142)	16.8 (3)	125.00%	356 (356)

Analysis Method:

IACA-147	ASTM D-3330/M	ASTM D-3330/M	ASTM D-3759	ASTM D-3759	
----------	---------------	---------------	-------------	-------------	--

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632

03/02/21

hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060