

Technical Data Sheet

776

COLD TEMPERATURE PACKAGING TAPE

DESCRIPTION:

BOPP carton sealing tape specially formulated to maintain high adhesion and tack in freezing conditions. RoHS compliant and suitable for indirect food packaging contact.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Sealing boxes in low-temperature environments such as produce packaging, food processing plants, non-heated warehouses, and moving boxes in cold temperatures.

CONSTRUCTION:

Backing:	Adhesive:
BOPP	Hot melt

Color:	Standar Lenght:
Clear	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
1.8 (0.046)	49.4 (550)	6 (65)	22 (4)	170

Analysis Method:

IACA-094	ASTM D-3330/M	ASTM D-3330/M	ASTM D-3759	ASTM D-3759
----------	---------------	---------------	-------------	-------------

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
11/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060