

DESCRIPTION:

Crepe paper masking tape with natural rubber-resin adhesive. Provides excellent conformability and clean removal. Resistant to solvents, water, and oils. Withstands bake cycles up to 185°F (85°C) for one hour.

Commonly used for plywood patching, screen-printing, and general masking in painting, office, or workshop applications.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:



**BUNDLING
& STRAPPING**



**HOME & SCHOOL
PROJECTS**



**MASKING
WINDOWS/DOORS**



AUTOMOTIVE



PAINTING

PRODUCT ATTRIBUTES

Thickness mils(mm)	Adhesion to Backing oz/in (gr/cm)	Adhesion to steel oz/in (gr/cm)	Tensile Strength lb/in (kg/cm)	Elongation (%)	TEMPERATURE °F (°C)
5 (0.13)	17.5 (195.3)	28 (315)	16 (2.8)	6.0	176 (80)

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

CONSTRUCTION:

STANDARD LENGTH (mm x m)	BACKING	COLOR	ADHESIVE:
 48 x 50 JUMBO	 CREPE PAPER	 PALE BAIGE	 RUBBER - RESIN

Guarantee:

Hystik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.