

DESCRIPTION:

Premium flatback tape developed with a rigid backing to provide stiffness and security during splices.

Manufactured with high performance adhesive that resists humidity and temperature conditions up to 400 °F.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:



**CARTON
SEALING**



SPLICING



**FLOORING
PROTECTION**

PRODUCT ATTRIBUTES

Thickness mils(mm)	Adhesion to Backing oz/in (gr/cm)	Adhesion to steel oz/in (gr/cm)	Tensile Strength lb/in (kg/cm)	Elongation (%)	TEMPERATURE °F (°C)
9.0 (0.23)	21 (235)	73 (815)	50 (8.9)	3	400 (204)

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

CONSTRUCTION:

STANDARD LENGTH (mm x m)	BACKING	COLOR	ADHESIVE:
48 x 55 JUMBO 72 x 50	FLAT BACK PAPER	BLUE	RUBBER - RESIN

Guarantee:

Hystik guarantees its tapes to be free from defects in materials and workmanship. This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices. It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.