

Technical Data Sheet

885

FLATBACK PACKAGING TAPE

DESCRIPTION:

General purpose light brown flatback tape.
Excellent for sealing, splicing, and packaging.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

General purpose sealing, splicing, and packaging applications.

CONSTRUCTION:

Backing:	Adhesive:
Flat Back Paper	Rubber - Resin

Color:	Standar Lenght:
Light Brown	24mmX50m 48mmX50m 72mmX50m 96mmX50m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Adhesion to Backing oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %	Temperature °F (°C)
7 (0.178)	15.7 (175)	43 (480)	34 (6.1)	8.5	50 - 140 (50 - 140)

Analysis Method:

IACA-094	ASTM D-3330/M	ASTM D-3330/M	ASTM D-3759	ASTM D-3759	
----------	---------------	---------------	-------------	-------------	--

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
05/06/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060