Technical Data Sheet

890 Tape 890 Double Coated Flatback tape

DESCRIPTION:

Medium performance tape of 7.7 mils thickness with a paper backing and rubber-resin adhesive in both sides. Medium adhesion and high cohesion.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Used to bond leather products, publicity materials, tags for identify areas and leather marking. Tape designed for Golf club manufacture and golf grip replacement and repair.

CONSTRUCTION:

Backing:	Adhesive:
Flatback paper	Rubber - Resin

Color:	Standar Lenght:
	48mmX10m 50mmX33m 12mmX33m 19mmX33m

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Internal Steel Adhesion oz/in (g/cm)	External Steel Adhesion oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
7.7 (0.195)	60.5 (675)	56 (625)	33 (5.9)	2.80%
Analysis Method:				
IACA-0194	*ASTM D-3330/M*	*ASTM D-3330/M*	*ASTM D-3759*	*ASTM D-3759*

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.
Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.
This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.
It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.
Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
30/05/25 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060