

### DESCRIPTION:

This high performance flatback paper tape is designed for splicing in the corrugated industry and sealing boxes. It has an acrylic adhesive that provides excellent adhesion and temperature resistance. Has a good tensile strength and is resistant to moist conditions. High initial tack. It has a liner for easy application.

Specially developed to be used on splicing in the corrugated industry for high tension and temperature demanding processes. It can also be used for sealing boxes and general purpose packaging. Excellent performance in cold climates.



\*Product presentation may be different than picture.

### SPECIALLY DESIGNED FOR:



CARTON SEALING



SPLICING



TEMPERATURE RESISTANCE



GENERAL PACKAGING

### PRODUCT ATTRIBUTES

Thickness mils(mm)	Adhesion to Backing oz/in (gr/cm)	Adhesion to steel oz/in (gr/cm)	Tensile Strength lb/in (kg/cm)	Elongation (%)	TEMPERATURE °F (°C)
8.8 (0.22)	22.3 (250)	151.0 (1690)	51.5 (9.2)	4	302 (150)

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

### CONSTRUCTION:

STANDARD LENGTH (mm x m)	BACKING	COLOR	ADHESIVE:
 48 x 50    96 x 50 72 x 50	 PAPER	 BLUE	 SOLVENT ACRYLIC

### Guarantee:

Hystik guarantees its tapes to be free from defects in materials and workmanship. This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices. It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

896, High performance flat-back paper splicing tape.