

Technical Data Sheet

930

VENTING TAPE

DESCRIPTION:

Venting tape is a non-woven pressure-sensitive tape made with an acrylic adhesive, delivering good outgassing performance in applications requiring vapor permeability.



*Product presentation may be different than picture.

SPECIALLY DESIGNED FOR:

Specially designed for flooring industry applications such as seaming tape requiring vapor permeability, insulated panel manufacturing, and refrigerator production lines to support polyurethane foam outgassing.

CONSTRUCTION:

Backing:	Adhesive:
Non-woven	Acrylic

Color:	Standar Lenght:
White	

PRODUCT ATTRIBUTES:

Thickness mils (mm)	Adhesion to Steel oz/in (g/cm)	Tensile Strength lb/in (kg/cm)	Elongation %
4.4 (0.11176)	22 (248)	7 (1.2)	1280.00%

Analysis Method:

IACA-094	ASTM D-3330/M	ASTM D-3759	ASTM D-3759
----------	---------------	-------------	-------------

Note: All figures shown are typical average values obtained from evaluations to fresh cut rolls and should not be considered as guaranteed specifications. Customer's entire responsibility is to ensure that product is suitable for the intended use.

Warranty: hyStik guarantees its tapes to be free from defects in materials and workmanship.

This guarantee does not cover product performance for any specific goal, purpose, or application, nor does it include issues arising from the method of use, user habits, or particular application practices.

It is the buyer's responsibility to determine whether the product is suitable for their specific intended use.

Liability is limited to the purchase price of the product supplied. hyStik reserves the right to modify product specifications and formulations at any time without prior notice.

Industrias Tuk, S.A. de C.V. Blvd Carlos Salinas de Gortari Col. Valle del Mezquital, Apodaca, NL México CP 66632
20/05/26 hyStik, Inc 12941 North Freeway, Suite 550, Houston TX, 77060