

hyStik®

adhesive tapes







INDUSTRIAL PROGRAM



DOWNLOAD OUR
DIGITAL BROCHURE

REV.01.2025

PE TAPES

TAPE	DESCRIPTION	THICKNESS (mils)	ADHESION TO STEEL (oz./in.)	TENSILE STRENGTH (lb./in.)
340	<p>General-purpose marking tape. Ideal for marking pedestrian traffic areas, floor sections, cable runs, and hazard zones. Available in multiple color combinations for visibility and identification.</p> 	6.3	67	13
373	<p>Low adhesion protection tape. Very conformable and water resistant. Up to 30 days UV resistant with clean removal. Ideal for masking and protection applications on smooth surfaces such as PVC frames, aluminum, steel, plastic, glass, etc. It is easy to unwind and tear by hand.</p> 	5.0	22	11
376	<p>Ideal to mask windows and doors during stucco applications. Excellent adhesion to plastic sheeting. It can be used in construction, restoration, abatement, polyethylene splicing, surface protection, plastic hanging and closing plastic bags along with many other industrial applications. Available in red and white.</p> 	7.0	58	14
377	<p>Stiff polyethylene backed tape. Non-UV. Excellent adhesion to plastic sheeting. It can be used in construction, restoration, abatement, polyethylene splicing, surface protection, plastic hanging and closing plastic bags along with many other industrial applications. Available in white color.</p> 	9.0	110	19
378	<p>Single coated UV resistant tape, heavy-duty, made of tough polyethylene backing and synthetic rubber adhesive. Film and adhesive formulated to resist degradation by exposure to UV up to 60 days, leaves no residue upon removal, and maintains watertight seal in all weather conditions. Available in red and white.</p> 	7.0	71	14
379	<p>UV version of 377 tape. Available in white color.</p> 	9.0	123	19

PACKAGING AND SEALING TAPE

TAPE	DESCRIPTION	THICKNESS (mils)	ADHESION TO STEEL (oz / in)	TENSILE STRENGTH (lb / in)	ELONGATION (%)
------	-------------	------------------	-----------------------------	----------------------------	----------------

HOT MELT CARTON SEALING

883	<i>Utility grade. Reliable adhesion for everyday box sealing.</i>	1.6	49	21	160
872	<i>Production grade. Designed for efficient, consistent closure in high-volume lines.</i>	1.8	52	23	160
884	<i>High performance for demanding applications requiring strong hold.</i>	2.0	53	25	170
866	<i>Premium grade. Ideal for heavy or overfilled cartons.</i>	2.5	55	30	180
868	<i>Heavy-Duty. Used for securing heavy or high-value packages.</i>	3.0	58	34	190

ALSO AVAILABLE IN LOCK PRINT

ACRYLIC

752	<i>Utility grade. Economic solution for light packaging.</i>	1.6	23	19	160
755	<i>Production grade. Balanced performance and versatility.</i>	1.8	25	21	160
760	<i>High Performance. Superior holding power on tough surfaces.</i>	2.0	27	25	170
762	<i>Performance grade. For an array of medium duty packaging applications.</i>	2.2	26	28	180
765	<i>Premium grade. Ideal for cold temperature, refrigerator and freezer tape.</i>	2.5	28	30	180
767	<i>Heavy Duty. Recommended cold environments when strong hold is required.</i>	3.0	30	34	190

ALSO AVAILABLE IN LOCK PRINT



PACKAGING AND SEALING TAPE

TAPE	DESCRIPTION	THICKNESS (mils)	ADHESION TO STEEL (oz./in.)	TENSILE STRENGTH (lb./in.)	ELONGATION (%)
CARTON SEALING SPECIALTIES					
786	Production grade surface printable carton sealing tape designed to be printed on without chemicals or corona treatment.	1.8	47	23	160
778	High performance surface printable carton sealing tape for cold application.	2.0	48	24	160
878	Surface printable carton sealing tape designed for roll-to-roll printing applications.	2.0	49	23	170
789	Premium grade surface printable carton sealing tape.	2.5	52	30	180

SURFACE PRINTABLE HOT MELT BOPP

FREEZER

776	Cold temperature hot melt BOPP tape. Performs in freezer and low-temp environments.	1.8	42	23	160
------------	---	-----	----	----	-----

LOCK PRINT

YOUR BRAND, YOUR MESSAGE – PRINTED PERMANENTLY, PERSONALIZED SECURELY. ADD YOUR LOGO HERE AND ELEVATE YOUR PACKAGING!



FLAT BACK TAPES


TAPE	DESCRIPTION	THICKNESS (mils)	ADHESION TO STEEL (oz./in)	TENSILE STRENGTH (lb./in)	ELONGATION (%)
FLATBACK PAPER					
885	General Purpose-light brown color. Excellent for sealing, splicing, and packaging.	7.0	38	39	9
886	Premium flatback-dark brown color tape with rigid backing. Ideal for cardboard operations like core starting, splicing and core manufacturing.	7.7	68	53	3
887	White flatback. PH neutral and surface printable. Available for water and solvent inks.	8.0	52	29	3
877	High performance-Blue color. Developed with high adhesion and quick-stick adhesive. Built for high-temp industrial splicing up to 400°F.	9.0	73	50	3
896	Ultra High Performance-Blue. Lined. For extreme cold environment splicing operations and high-tension cardboard core manufacturing.	8.8	151	52	4




MASKING TAPES


TAPE	DESCRIPTION	THICKNESS (mils)	ADHESION TO STEEL (oz./in)	TENSILE STRENGTH (lb./in)	ELONGATION (%)
793	<i>General Purpose-White. For marking, bonding, packaging and day-to-day uses.</i>	4.2	47	16	8
798	<i>High temp tape, natural rubber adhesive. Solvent, water and oil resistant. Withstands bake temps up to 185°F for 1 hour. Utilized as plywood patch tape and for screen-printing applications (T-shirt printers).</i>	5.0	28	16	6
803	<i>General Purpose-White. With natural rubber adhesive. Provides reliable performance for everyday applications where medium adhesion is needed.</i>	5.1	39	16	6
825	<i>Light Blue color. 7-day medium-duty. Excellent for multipurpose indoor/outdoor painting.</i>	5.0	23	17	6
835	<i>Blue color. 14-day blue painter's tape. Clean removal for indoor/outdoor use.</i>	6.2	22	18	7
827	<i>Very conformable. Resists paint bleed and perform up to 194°F. available in Yellow.</i>	6.0	27	17	7
832	<i>Performance grade- Yellow color, very flexible and high heat resistance up to 260°F.</i>	6.8	26	25	12
836	<i>Premium quality-Green, with a smooth, flexible and strong crepe paper backing. Highly conformable and with good resistance to break. Removes clean after exposure to 260°F (127°C).</i>	7.0	32	25	12
841	<i>High performance-cream color. Clean removal from a variety of surfaces after exposure up to 325°F (163°C) for 30 minutes. Ideal for industrial, marine and some electronic applications.</i>	7.0	34	25	10
850	<i>Ultra-thin washi (rice paper) "sharpline" masking tape for fine lines and clean edges; acrylic adhesive; designed for indoor/outdoor use up to 60 days with clean removal.</i>	3.2	19	17	5


OTHER SPECIALTY TAPES

TAPE	DESCRIPTION	THICKNESS (mils)	ADHESION TO STEEL (oz / in)	TENSILE STRENGTH (lb / in)	ELONGATION (%)
970 	<i>Polypropylene-backed filament tape reinforced with fiberglass filaments. Designed for light to medium-duty strapping, bundling, and reinforcement.</i>	4.0	60	110	3.5

FRICTION TAPES

313 	<i>General purpose black color friction tape, cotton cloth backing. Provides mechanical protection against abrasion and penetration of cables, splices and harnesses. Non-slip surface on tool/sport handles.</i>	13.3	-	46	5
---	---	------	---	----	---

315 	<i>Black colored, flexible and conformable cotton cloth insulating tape with non-corrosive adhesive. Excellent abrasion resistance, higher tensile strength, easy hand tear.</i>	15.0	-	67	5
---	--	------	---	----	---

316 	<i>Black color, high-quality cotton friction tape coated on both sides with rubber adhesive. Provides mechanical protection against abrasion/penetration of cables and harnessing.</i>	13.0	-	46	5
---	--	------	---	----	---

DOUBLE-SIDED TAPES

TAPE	DESCRIPTION	THICKNESS (mils)	ADHESION TO STEEL (oz / in)	TENSILE STRENGTH (lb / in)	ELONGATION (%)
890	<i>Paper carrier double-coated tape. Medium adhesion for golf gripping and indoor use like carpet installation.</i>	7.0	55	37	3
410	<i>Black colored flexible polyester double-coated tape. High adhesion to varied surfaces and LSE materials. Great option for splicing.</i>	6.2	102	17	125



CONTACT US

we're at your service

HEADQUARTERS

TEL +52(81) 8221 7425
infona@hystik.com

NORTH AMERICA

TEL (281) 784 7711
infona@hystik.com

CENTRAL AMERICA

TEL (503) 2289 4798
infoca@hystik.com

COLOMBIA

TEL 57 (1) 4 91 11 36, 37 & 38
servicioalcliente@suplimos.com.co



www.hystik.com

[/hystikInc](https://www.instagram.com/hystikInc)

infona@hystik.com